

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Aquatuning SysClean-HPD Hochleistungsentkalker

Product group: Mixtures

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Manual maintenance (cleaning and repair) of machinery

1.3. Details of the supplier of the safety data sheet

Company name:	Aquatuning GmbH	
	Hauptsitz	
Street:	Carl-Zeiss Str. 2	
Place:	D-33758 Schloss Holte - Stukenbrock	
Telephone:	05207 95846-140	Telefax: 05207 95846-222
e-mail:	info@aquatuning.de	
Contact person:	Waldemar Balzer	Telephone: 05207 95846-171
e-mail:	w.balzer@aquatuning.de	
Internet:	www.aquatuning.de	
Responsible Department:	Abteilung Produktmanagement	

1.4. Emergency telephone number:

+49 (0) 6131 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eye damage.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Formic acid ... %

Signal word: Danger

Pictograms:

**Hazard statements**

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P264 Wash Hände thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 2 of 8

P310 present and easy to do. Continue rinsing.
 Immediately call a POISON CENTER/doctor.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
5329-14-6	sulfamic acid, sulphamic acid, sulphamidic acid	25 - < 30 %
	226-218-8	
	016-026-00-0	
	Eye Irrit. 2, Skin Irrit. 2, Aquatic Chronic 3; H319 H315 H412	
64-18-6	Formic acid ... %	10 - < 15 %
	200-579-1	
	607-001-00-0	
	Skin Corr. 1A; H314	
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	10 - < 15 %
	203-961-6	
	603-096-00-8	
	Eye Irrit. 2; H319	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

If unconscious place in recovery position and seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

4.3. Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder Water spray jet

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 3 of 8

5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Dilute with plenty of water.

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Provide adequate ventilation.

Disposal: see section 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep locked up and out of reach of children.

Wash hands before breaks and after work.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Further information on handling

When using do not eat, drink, smoke, sniff.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Remove contaminated, saturated clothing.

Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep locked up and out of reach of children.

Keep container tightly closed and in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
64-18-6	Formic acid	5	9.6		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Protective and hygiene measures

- When using do not eat, drink, smoke, sniff.
- Remove contaminated, saturated clothing.
- Avoid contact with skin, eyes and clothes.

Eye/face protection

Eye glasses with side protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
NBR (Nitrile rubber)

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state: Liquid
 Colour: colourless
 Odour: Mild

pH-Value (at 20 °C): <1

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: 100 °C
 Sublimation point: not determined
 Softening point: not determined
 Pour point: not determined
 : not determined
 Flash point: not determined

Flammability

Solid: not determined
 Gas: not determined

Explosive properties

The study does not need to be conducted for explosives.

Density (at 15 °C): 1,105 g/cm³ DIN 51757

Water solubility: very soluble

Test method

ISO 10156

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 5 of 8

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No known hazardous reactions.

10.5. Incompatible materials

No known hazardous reactions.

10.6. Hazardous decomposition products

No known hazardous reactions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
5329-14-6	sulfamic acid, sulphamic acid, sulphamidic acid				
	oral	LD50 mg/kg	3160	Rat	
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 mg/kg	5660	Rat	
	dermal	LD50 mg/kg	4120	Rabbit	

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 6 of 8

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
5329-14-6	sulfamic acid, sulphamic acid, sulphamidic acid					
	Acute fish toxicity	LC50 mg/l	70,3	96 h	Pimephales promelas	
64-18-6	Formic acid ... %					
	Acute fish toxicity	LC50 mg/l	46 - 100	96 h	Leuciscus idus	IUCLID
	Acute algae toxicity	ErC50	27 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	34,2	48 h	Daphnia magna	IUCLID
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus sp.	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-18-6	Formic acid ... %	-0,54
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56 (25°C)

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the mixture itself.

12.6. Other adverse effects

There are no data available on the mixture itself.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Waste disposal number of waste from residues/unused products

110106 WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); acids not otherwise specified; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information
Land transport (ADR/RID)
14.1. UN number:

UN 3264

14.2. UN proper shipping name:

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 7 of 8

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Classification code: C1

Special Provisions: 274

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 80

Tunnel restriction code: E

Marine transport (IMDG)

14.1. UN number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Special Provisions: 223, 274

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8



Special Provisions: A3 A803

Limited quantity Passenger: 1 L

Passenger LQ: Y841

Excepted quantity: E1

IATA-packing instructions - Passenger: 852

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 856

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aquatuning SysClean-HPD Hochleistungsentkalker

Revision date: 28.02.2018

Product code: 30000

Page 8 of 8

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: Formic acid ... %

Entry 55: 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)